TECHNICAL SPECIFICATIONS X-DUO 068



BUILT TO PERFORM



HIAB X-DUO 068 **TECHNICAL SPECIFICATIONS**

Technical Data	X-DUO 068 D1	X-DUO 068 D-2	X-DUO 068 D-3
Lifting capacity			
Lifting capacity (ft-lbs)	44 254	43 516	42 041
	Outreach		
Standard outreach (ft-lbs)	7' 3" - 6 040 12' 6" - 3 572 17' 5" - 2 557 - -	8' 2" - 5 203 12' 10" - 3 395 17' 9" - 2 381 23' 8" - 1 764 -	9' 6" - 4 365 13' 2" - 3 175 18' 1" - 2 205 23' 11" - 1 587 30' 6" - 1 235
Outreach, hydraulic extensions (ft)	17' 9"	23' 11"	30' 6"
	Dil and tank		
Rec OilFlow Io (gal/min)	7	7	7
Rec OilFlow hi (gal/min)	8	8	8
Work pressure (psi)	4 206	4 206	4 206
	Slewing		
Slewing torque (ft-lbs)	6 240	6 240	6 240
Slewing angle (degrees)	410	410	410
[Dimensions	1	
Height in folded position (in)	6' 3"	6' 3"	6' 3"
Width in folded position (in)	6' 4"	6' 7"	7' 1"
	Weights		
Weight of crane w/o stabilizers (lbs)	1 742	1 918	2 094
Additional weight of hose & pipe kit (lbs)	132	132	132
Weight of stabilizers (lbs)	353	353	353
Inst	allation space	:	
Installation space needed (in)	2' 2"	2' 2"	2' 2"
► HIAB X-DUO 068D-3	" <u>23'1</u> " <u>30'7</u> "	<u></u>	



Disclaimer. This table shows a few examples of models, and represents some of all options available. With the opportunity to configure your crane, we can provide you with a crane perfectly tailored to your needs. Please contact your local Hiab sales representative for more information on the variety of options we can offer. We reserve the right to make changes. Illustrations, drawings and data are not always in accordance with the latest version or standard model in production. The models in the pictures may present special equipment or colors.

790

BUILT TO PERFORM

PRINCETON truck



4370

ADC lbs

lbs 4010 3170

2910

2200

2030

1590

1460

1230

1100