

TECHNICAL SPECIFICATIONS

X-HIPRO 1058



BUILT TO PERFORM



HIAB X-HIPRO 1058

TECHNICAL SPECIFICATIONS

Technical Data	X-HIPRO 1058 EP-4	X-HIPRO 1058 EP-5	X-HIPRO 1058 EP-6	X-HIPRO 1058 EP-7	X-HIPRO 1058 EP-8
Lifting capacity					
Lifting capacity (ft-lbs)	619 552	612 914	608 489	592 262	585 624
Outreach					
Standard outreach (ft-lbs)	15' 5" - 39 683	15' 5" - 39 683	15' 5" - 39 683	14' 5" - 39 683	14' 5" - 39 683
	19' 8" - 31 306	20' 4" - 29 762	20' 4" - 29 322	20' - 28 660	20' 8" - 27 117
	25' 3" - 24 251	26' 3" - 22 708	26' 3" - 22 267	25' 7" - 21 605	26' 3" - 20 503
	31' 6" - 19 180	32' 6" - 18 078	32' 6" - 17 637	31' 2" - 17 196	31' 10" - 16 094
	38' 1" - 15 873	39' 1" - 14 771	39' 1" - 14 551	37' 5" - 13 669	38' 1" - 12 787
	-	46' 3" - 12 346	46' 3" - 12 125	44' - 11 464	44' 7" - 10 472
	-	-	53' 6" - 10 362	50' 2" - 9 811	50' 10" - 8 929
	-	-	-	57' 1" - 8 488	57' 9" - 7 606
	-	-	-	63' 8" - 7 606	64' 4" - 6 724
	-	-	-	-	71' 6" - 5 997
	-	-	-	-	78' 1" - 5 468
Outreach, hydraulic extensions (ft)	38' 9"	46' 7"	53' 10"	64' 8"	78' 9"
Oil and tank					
Rec OilFlow lo (gal/min)	26	26	26	26	26
Rec OilFlow hi (gal/min)	32	32	32	32	32
Work pressure (psi)	5 511	5 511	5 511	5 511	5 511
Slewing					
Slewing torque (ft-lbs)	50 154	50 154	50 154	44 254	44 254
Slewing angle (degrees)	999	999	999	999	999
Dimensions					
Height in folded position (in)	8' 3"	8' 6"	8' 6"	8' 3"	8' 6"
Width in folded position (in)	8' 4"	8' 4"	8' 4"	8' 4"	8' 4"
Weights					
Weight of crane w/o stabilizers (lbs)	14 304	15 144	15 547	17 406	18 268
Additional weight of hose & pipe kit (lbs)	247	265	291	320	408
Weight of stabilizers (lbs)	3 109	3 109	3 109	3 109	3 109
Installation space					
Installation space needed (in)	5' 2"	5' 2"	5' 2" - 6'	5' 8" - 6' 4"	5' 8" - 6' 3"

HIAB X-HIPRO 1058 E-10													
ft	9'10"	14'5"	20'8"	26'3"	31'10"	38'1"	44'7"	50'10"	57'9"	64'4"	71'6"	78'1"	
ADC lb	48500	39680	27120	20500	16090	12790	10470	8930	7610	6720	6000	5470	
lb	36820	24910	18740	14550	11680	9480	8050	6830	6000	5340	4890		
* Special hook in heavy lift attachment													

Disclaimer. This table shows a few examples of models, and represents some of all options available. With the opportunity to configure your crane, we can provide you with a crane perfectly tailored to your needs. Please contact your local Hiab sales representative for more information on the variety of options we can offer. We reserve the right to make changes. Illustrations, drawings and data are not always in accordance with the latest version or standard model in production. The models in the pictures may present special equipment or colors.

BUILT TO PERFORM

Hiab (Nasdaq Helsinki: HIAB) is a leading provider of smart and sustainable on road load-handling solutions, committed to delivering the best customer experience every day with the most engaged people and partners. Hiab's premium equipment includes HIAB and EFFER loader cranes, MOFFETT and PRINCETON truck mounted forklifts, MULTILIFT skiploaders and hooklifts, GALFAB roll-off cable hoists, and WALTCO tail lifts, and the service brand HIPERFORM, a comprehensive suite of smart solutions that help maximize the life-cycle value of Hiab's equipment. As the industry pioneer, Hiab continues to make on road load-handling smarter, safer and more sustainable to build a better tomorrow.

www.hiabgroup.com

